

PRODUCT TECHNICAL SHEET



Applications

High performance and finishing sandpaper, designed for dry sanding plates, primers, lacquers, sealers, and varnishes in the automotive and furniture markets. **Contains anti-caking layer.**

Composition & Technical Data

- Abrasive: Brown aluminum oxide;
- Back: Paper;
- Adhesive: Resin on resin:
- Layer: Open;
- Available grains:

 P40
 P80
 P120
 P150
 P220

 P320
 P400
 P600
 P800

- Discs: 6" Feather back and 6 holes
- Package: 40 Discs (only grain 40).
- Package: 50 Discs.

T273 - DRY SANDPAPER DISC

CHARACTERISTIC ANTI-CAKING OF Cleaner working environment; Easy sanding; SPECIAL PAPER OF High flexibility when sanding; FEPA STANDARD • Dry sanding; • Cleaner working environment; • Easy sanding; • Great resistance at work; • High flexibility when sanding; • Internacional standard • Better sanding uniformity

SPECIAL CHARACTERISTIC

Anti-caking zinc stearate layer.

STORAGE

This product must be stored in its original packaging at a temperature between 15° and 27° C and relative humidity between 35% and 50% and away from floors, windows and damp places. Under the above conditions, the product validity is 5 years.









